



Šroubení pro stlačený vzduch

z mosazi – poniklované provedení



Šroubení s vnějšími kuželovými závity							
	Obj. č.	Závit 1	Délka závitu	Závit 2	Délka závitu	l	SW
•	A006-1818	R 1/8"	7,5	R 1/8"	7,5	19	12
•	A006-1814	R 1/8"	7,5	R 1/4"	10	22,5	14
•	A006-1838	R 1/8"	7,5	R 3/8"	10	22,5	17
•	A006-1414	R 1/4"	10	R 1/4"	10	25	14
•	A006-1438	R 1/4"	10	R 3/8"	10	25	17
•	A006-1412	R 1/4"	10	R 1/2"	12	28	22
•	A006-3838	R 3/8"	10	R 3/8"	10	25	17
•	A006-3812	R 3/8"	10	R 1/2"	12	28	22
•	A006-1212	R 1/2"	12	R 1/2"	12	30	22
•	A006-1234	R 1/2"	12	R 3/4"	14	32	27
•	A006-3434	R 3/4"	14	R 3/4"	14	34	27
•	A006-3410	R 3/4"	14	R 1"	16	37	34
•	A006-1010	R 1"	16	R 1"	16	39	34



Mufny s vnitřními závity					
	Obj. č.	Závit 1	Závit 2	l	SW
•	A007-1818	G 1/8"	G 1/8"	15	14
•	A007-1814	G 1/8"	G 1/4"	19	17
•	A007-1838	G 1/8"	G 3/8"	20	22
•	A007-1414	G 1/4"	G 1/4"	22	17
•	A007-1438	G 1/4"	G 3/8"	23	22
•	A007-1412	G 1/4"	G 1/2"	26	17
•	A007-3838	G 3/8"	G 3/8"	24	22
•	A007-3812	G 3/8"	G 1/2"	26	27
•	A007-1212	G 1/2"	G 1/2"	29	27
•	A007-1234	G 1/2"	G 3/4"	30	32
•	A007-3434	G 3/4"	G 3/4"	32	32
•	A007-3410	G 3/4"	G 1"	34	38
•	A007-1010	G 1"	G 1"	34	38



Záslepky se šestihranem a s vnějším trubkovým závitem					
	Obj. č.	Závit	Délka závitu	l	SW
•	A008-18	G 1/8"	5	10	14
•	A008-14	G 1/4"	6	10	17
•	A008-38	G 3/8"	8	13	19
•	A008-12	G 1/2"	8	13	24
•	A008-34	G 3/4"	9	14	30
•	A008-10	G 1"	11	18	36



Záslepky s imbusem a osazením, s vnějším trubkovým závitem						
	Obj. č.	Závit	Délka závitu	l	Průměr	SW
•	A009-M5	M5	4	6,5	8	2,5
•	A009-18	G 1/8"	7	9,5	15	3
•	A009-14	G 1/4"	8	11	18	6
•	A009-38	G 3/8"	9	12,5	21	8
•	A009-12	G 1/2"	11	14,5	26	10



Záslepky s imbusem, bez osazení, s vnějším trubkovým závitem					
	Obj. č.	Závit	Délka závitu	Hloubka SW	SW
•	A012-18	G 1/8"	7,5	4	5
•	A012-14	G 1/4"	10	5	6
•	A012-38	G 3/8"	10	6	8
•	A012-12	G 1/2"	12	8	10