











## ARMORVIN HNA

913040



Plasticized PVC hose with embedded galvanized steel spiral, for suction and delivery of liquids and liquid food stuffs.

### DETAILS

	SMOOTH SURFACE	*****
	FLEXIBILITY	****
	ABRASION RESISTANCE	***
	TEMPERATURE RANGE	-5 °C 65 °C
	CHEMICAL RESISTANCE	PVC Table
	CRUSHING RESISTANCE	***
	FOR FOOD	EU according to Declaration of Conformity. FDA according to Declaration of Conformity
	O-PHTALATE FREE	*****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23 °C m/H <sub>2</sub> O	working press. at 23 °C r.1.3 bar	bursting press. at 23 °C bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
10	3/8	10	16	8.5	7	21	20	3	0.8	6.5	right	155	60	In stock
12		12	18	8.5	7	21	25	3	0.8	7	right	180	60	In stock
14		14	20	8.5	6	18	30	3	0.8	7.5	right	200	60	In stock
16	5/8	16	22	8.5	6	18	35	3	0.8	7.5	right	225	60	In stock
18		18	24.5	8.5	6	18	40	3.25	1	8	right	280	60	In stock
19	3/4	19	26	8.5	5	15	45	3.5	1	8	right	310	60	On demand
20		20	27	8.5	5	15	50	3.5	1	8	right	340	60	In stock
22	7/8	22	29	8.5	5	15	55	3.5	1	8.5	right	360	60	In stock
25	1	25	33	8.5	5	15	60	4	1.4	13.5	right	510	60	In stock
30		30	39	8.5	4.5	13.5	70	4.5	1.4	13.5	right	600	60	On demand
32	1 1/4	32	41	8.5	4.5	13.5	75	4.5	1.4	13.5	right	650	60	In stock
35		35	44	8.5	4	12	80	4.5	1.4	14.5	right	730	60	In stock
38	1 1/2	38	47	8.5	4	12	90	4.5	1.6	15	right	800	30	In stock
40		40	49.5	8.5	3	9	95	4.75	1.6	15	right	870	30	In stock
45	1 3/4	45	55	8	3	9	110	5	1.8	15	right	1100	30	In stock
50	2	50	60	8	3	9	125	5	1.8	16	right	1200	30	In stock
55		55	66	8	3	9	130	5.5	1.8	16.5	right	1380	30	On demand
60		60	72	8	2.5	7.5	140	6	2.5	20	right	1800	30	In stock
63	2 1/2	63	75	8	2.5	7.5	150	6	2.5	20	right	1880	30	In stock
70		70	83	8	2	6	170	6.5	2.5	20	right	2200	30	On demand
75		75	89	7	2	6	200	7	2.5	20	right	2500	30	In stock
80		80	94	7	2	6	220	7	2.5	20	right	2700	30	In stock
90	3 1/2	90	104	7	2	6	260	7	2.5	20	right	2900	30	On demand
100		100	114	7	2	6	300	7	2.5	19	right	3250	30	In stock

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)