




## Potrubi systém SICOAIR

pro stlačený vzduch, pro světlosti DN 20 až DN 65



Odbočky s vnitřním závitem SRQ							
Obj. č.	Velikost	Rozměry (mm)				Hmotnost (g)	Balení (ks)
		A	B	C	D		
SRQ-1220	1/2" × 20 mm	62	37	1/2"	55	43	1
SRQ-1225	1/2" × 25 mm	65	40	1/2"	57	63	1
SRQ-1232	1/2" × 32 mm	78	45	1/2"	59	102	1
SRQ-1240	1/2" × 40 mm	86	51	1/2"	69	121	1
SRQ-1250	1/2" × 50 mm	86	53	1/2"	78	122	1
SRQ-1263	1/2" × 63 mm	94	71	1/2"	93	235	1
SRQ-3425	3/4" × 25 mm	69	53	3/4"	52	69	1
SRQ-3432	3/4" × 32 mm	78	45	3/4"	60	107	1
SRQ-3440	3/4" × 40 mm	86	51	3/4"	72	123	1
SRQ-3450	3/4" × 50 mm	86	53	3/4"	79	126	1
SRQ-3463	3/4" × 63 mm	95	71	3/4"	96	238	1



Odbočky se dvěma výstupy SR258 / SR208							
Obj. č.	Velikost	Rozměry (mm)				Hmotnost (g)	Balení (ks)
		A	B	C	D		
SR258-1225	1/2" × 25 mm	78	95	40	1/2"	170	1
SR258-1232	1/2" × 32 mm	78	95	40	1/2"	160	1
SR208-1240	1/2" × 40 mm	85	92	50	1/2"	255	1
SR208-1050	1" × 50 mm	134	146	80	1"	974	1
SR208-1063	1" × 63 mm	134	146	80	1"	841	1



Koncové krabice SR243							
Obj. č.	Vstupy	Výstup	Rozměry (mm)			Hmotnost (g)	Balení (ks)
			d	š	v		
SR243-1238	1 × 1/2"	1 × 3/8"	62	46	52	55	1
SR243-1212	2 × 1/2"	1 × 3/8"	62	46	52	55	1



Podstavce pro koncové krabice SR243					
Obj. č.	Rozměry (mm)			Hmotnost (g)	Balení (ks)
	d	h	v		
SR243-S	62	11	52	17	10

související zboží:

Šroubení  
str. 66



Úpravné jednotky  
str. 774



Spirálové hadice  
str. 470



Kohouty  
str. 565

